



NOTES: UNLESS OTHERWISE SPECIFIED

1. TOUCHSCREEN SPECIFICATIONS PER AUTOMOTIVE GRADE.
2. TOLERANCE ±.015 UNLESS NOTED OTHERWISE.
3. TOP CONDUCTIVE LAYER TO BE .007" THICK POLYESTER WITH AN ANTI-GLARE COATING.
4. THE CONNECTOR IS LOCATED ON THE LEFT SIDE OF THE PANEL.
5. PIN ONE LOCATION IS THE TOP PIN WHEN VIEWING WITH CABLE TO THE LEFT.
6. PIN OUT AS FOLLOWS:
 - PIN 1 - UPPER RIGHT
 - PIN 2 - LOWER RIGHT
 - PIN 3 - SENSE
 - PIN 4 - UPPER LEFT
 - PIN 5 - LOWER LEFT.
7. FCC TAIL IS TERMINATED USING AMP PINS 2-487406-4 AND HOUSING 487378-4 OR EQUIVALENTS.
8. NOMINAL PANEL THICKNESS IS .055" ±.008 (1.40 ±.20).

BERGQUIST TOUCH PRODUCTS			
301 WASHINGTON STREET CANNON FALLS, MN 55605			
TITLE: 7.0" DIAGONAL 5 WIRE TOUCHSCREEN			
DRN: PEH	DATE: 12/10/07	SCALE: 1:1	TOL: ±.015
CHKD: MLR	DATE: 12/14/07	PART NUMBER: 400397	REV: -
APVD:	DATE:		